



**SPECIFICATION NOTES:**

1. Wet pour coloured rubber to be installed to manufacturer's written instructions, including adhesion to concrete. Rubber to comply with AS4422 if surface is in a dedicated fall zone area.
2. Impact layer is required if in a dedicated fall zone area. Impact layer to be installed to manufacturer's written instructions and comply with AS4422.
3. Sub-grade for rubber to be installed to manufacturer's written instructions. Material to be specified by ICC representative.
4. Existing Sub-grade to be compacted to 95% AASHO Modified. Where the existing sub-grade is not suitable for compaction, excavate and replace with suitable fill material to achieve the specified rate of compaction.

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F				L	
E				K	
D				J	
C				I	
B				H	
A				G	
ORIGINAL ISSUE					

**IPSWICH CITY COUNCIL**  
 45 Roderick St  
 P.O. Box 191  
 Ipswich QLD 4305  
 Australia

Tel (07) 3810 7894  
 Tel (07) 3810 7927  
 Fax (07) 3810 7950

APPROVED

*[Signature]*

CHIEF OPERATING OFFICER (WPR)

DATE 29-7-13

**STANDARD DRAWING**

**PLAYSPACE - RUBBER WEAR PAD**

PARKS

**SP.95**

REV: A DRAWER: 100