



PLAN - ROUNDABOUT

(ACCESS STREET ONLY)

Kerb and Channel

NOTES

1. This is an example drawing only. It is the designer's responsibility to ensure that the individual design complies with the relevant standards.
2. Minimum diameter for area to be landscaped is 4m. Areas less than 4m Dia. shall be infilled with approved patterned concrete.
3. A clear vehicle swept area clear of signs, lightpoles and other obstructions shall be provided for 1.5m behind the kerb and channel where roundabout turning manoeuvres occur.
4. All linemarking and signage to be in accordance with MUTCD.
5. For pavement design requirements refer to Planning Scheme Policy 3 - General Works.
6. Concrete N25 in accordance with AS 1379 and AS 3600.
7. Reinforcing Fabric to AS4671, 50mm Top and Edge Cover, lap Fabric 250mm.

LEGEND

* Invert of kerb and channel.

Pavement, Refer Note 5

175mm Thick N25 Concrete with SL72 Steel Mesh.

Width in accordance with project drawings.

Kerb type SM5

Garden soil and mulch. Refer landscape plans.

5% min

Circulating Lane Width

50mm rounding.
50mm

100mm

For subsurface drainage refer Std Drg. SR.20.

SECTION THROUGH ROUNDABOUT

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F				L	
E				K	
D				J	
C			Notes 6 & 7 Added, Rev labels updated	I	
B			Amended to refer to New Town Plan.	H	
A			ORIGINAL ISSUE	G	

IPSWICH CITY COUNCIL
 45 Roderick St
 P.O. Box 191
 Ipswich QLD 4305
 Australia

Tel (07) 3810 7894
 Tel (07) 3810 7927
 Fax (07) 3810 7950

APPROVED
[Signature]
 CHIEF OPERATING OFFICER (ES)
 DATE 14.9.10

STANDARD DRAWING
 STANDARD ROUNDABOUT DETAILS

ROADWORKS
SR.29
 REV: C DRAWER: 100