



LEGEND

- Wire fixed to back of posts

NOTES

- A - Weldmesh Fence
- Gate and end posts to be 65x65x2 galvanised steel section to AS 1163 and AS 4792.
 - Intermediate posts to be 50x50x2 galvanised steel section to AS 1163 and AS 4792.
 - Panels to be fixed to posts using standard galvanised clips and galvanised M8 bolts.
 - Galvanising to AS 1214 and AS 4680.
 - Concrete N25 in accordance with AS 1379 and AS 3600.
 - Posts are to be vertical.
 - Raked panels are available for slopes up to 1 in 5.
 - Nuts to be spot welded to bolts as an anti-theft deterrent.
- B - Control Fence
- All barbed wire, plain wire, hinged joint fencing, staples and ring fasteners to be galvanised to AS 4534, AS 4680 and AS 4792.
 - Provide strainer panels at 100 to 140m spacing. Panels to be as for 'End Panels' with an extra 2/3.15mm wire brace as indicated by broken lines.
 - Posts may be tea-tree, split hardwood or sawn timber.
 - Where fences turn 90° adopt an end panel going away in each direction.
 - Dowels, Grade 250 to AS 3679, Galvanised to AS 4680
- C - General
- All dimensions in millimetres unless shown otherwise.
 - Reinforcing fabric to AS 4671, 50mm Top and Edge cover, Lap fabric 250mm.

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F				L	
E				K	
D				J	
C				I	
B				H	
A				G	

Notes A1, A2, A4, B1 & B5 Aust. Stds Updated. Note C2 added.
 Mowing strip made compulsory.
 ORIGINAL ISSUE

IPSWICH CITY COUNCIL
 45 Roderick St
 P.O. Box 191
 Ipswich QLD 4305
 Australia

Tel (07) 3810 7894
 Tel (07) 3810 7927
 Fax (07) 3810 7950

APPROVED

 CHIEF OPERATING OFFICER (ES)
 DATE 14-9-00

STANDARD DRAWING
WELDMESH FENCING AND CONTROL FENCE

ROADWORKS
SR.32
 REV: C DRAWER: 100