



RURAL RESIDENTIAL ACCESSWAY

APPLICABLE CRITERIA

New rural residential accessways must;

- a. Be no longer than 250m, measured from a currently maintained Council road,
- b. Provide access to no more than three (3) rural residential properties,
- c. Not provide "Through Access",
- d. Not provide access to non-residential uses.

NOTES

- 1. Refer SR.10 for Standard Verge and Access Profiles.
- 2. Minimum slope of table drain inverts shall be 0.5% (1 in 200).
- 3. Pavement shall be a minimum of 100mm compacted depth (CBR15), compacted to 100% (standard compaction).
- 4. Cross drainage shall be constructed to satisfy a minimum Q2 immunity. Where it can be demonstrated that drainage structures can not practically achieve Q2 immunity, a floodway may be constructed in accordance with the requirements of the Chief Operating Officer (COO) Works Parks and Recreation (WPR). Floodways must include cross road drainage to accommodate low flow events.
- 5. New accessways shall be centrally located within the the nominated road reserve unless approved otherwise.
- 6. All dimensions in metres unless shown otherwise.

LEGEND

⊗ Batter slopes where $H < 0.5m$. slope to be 1 in 6. Where $H \geq 0.5m$ slope to be 1 in 4 or as determined by Council's Engineer.

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F			L		
E			K		
D			J		
C			I		
B			H		
A			G		

ORIGINAL ISSUE

IPSWICH CITY COUNCIL
 45 Roderick St
 P.O. Box 191
 Ipswich QLD 4305
 Australia

Tel (07) 3810 7894
 Tel (07) 3810 7927
 Fax (07) 3810 7950

APPROVED

 CHIEF OPERATING OFFICER (WPR)
 DATE 12/3/12

STANDARD DRAWING

TYPICAL CROSS SECTION
 RURAL RESIDENTIAL ACCESSWAY

ROADWORKS

SR.41

REV: A DRAWER: 100