



NOTES

1. Location to be marked out or approved by ICC.
2. All dimensions and levels to be verified prior to construction.
3. Posts: 100x200mm F14 HWD class 1 bollards.
4. Rails: 200x75mm F14 HWD. Rails to be fixed to each post by 2xM12 galv. C.H. bolts positioned in the middle of the post and 60mm from rail edge.
5. Caster wheel: Fixed, non marking, solid rubber wheel, load capacity 200kg min. 100-150mm Ø. Caster wheel is to be welded to the gate, positioned 150mm from end of gate.
6. Galv. gate: 1800 width x 900mm high with 2 horizontal bars spaced equally between top and bottom rails. Weld gate hinges to post and gate.
7. Gate frame to be 50x25x1.6 RHS galv. Gate and post to be powdercoated to park colour scheme.

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F				L	
E				K	
D				J	
C				I	
B				H	
A				G	

IPSWICH CITY COUNCIL
 45 Roderick St
 P.O. Box 191
 Ipswich QLD 4305
 Australia

Tel (07) 3810 7894
 Tel (07) 3810 7927
 Fax (07) 3810 7950

APPROVED

 CHIEF OPERATING OFFICER (WPR)
 DATE 29-7-13

STANDARD DRAWING
FENCE - TIMBER TRAIL BIKE ENTRANCE DETERRENT

PARKS
SP.88
 REV: A DRAWER: 100