


SPECIFICATION NOTES:

1. Wet pour coloured rubber to be installed to manufacturer's written instructions, including adhesion to concrete. Rubber to comply with AS4422 if surface is in a dedicated fall zone area.
2. Impact layer is required if in a dedicated fall zone area. Impact layer to be installed to manufacturer's written instructions and comply with AS4422.
3. Sub-grade for rubber to be installed to manufacturer's written instructions. Material to be specified by ICC representative.
4. Existing Sub-grade to be compacted to 95% AASHO Modified. Where the existing sub-grade is not suitable for compaction, excavate and replace with suitable fill material to achieve the specified rate of compaction.

REVISIONS					
AMENDMENT	INITIALS	DATE	AMENDMENT	INITIALS	DATE
F				L	
E				K	
D				J	
C				I	
B				H	
A				G	
ORIGINAL ISSUE					


IPSWICH CITY COUNCIL
 45 Roderick St
 P.O. Box 191
 Ipswich QLD 4305
 Australia
 Tel (07) 3810 7894
 Tel (07) 3810 7927
 Fax (07) 3810 7950

APPROVED

 CHIEF OPERATING OFFICER (WPR)
 DATE 29-7-13

STANDARD DRAWING
PLAYSPACE - PLANTING AREA TO RUBBER
SOFTFALL/WEAR LAYER

PARKS
SP.97
 REV: A DRAWER: 100